

IN THE CLAIMS**Claims 1 - 14 Cancel**

Claim 15. (Currently Amended) The method of using a ramp as claimed in claim 14 16, wherein the method further comprises:

adding a second additional second ramp portion by placing said second additional second ramp portion on said at least one second ramp portion,

moving said vehicle until said tires are resting on said second additional second ramp portion.

Claim 16. (New) A method of using a ramp to raise wheels of a vehicle, and consequently the vehicle itself, off of the ground, said ramp comprising:

a first ramp portion,

said first ramp portion having a top surface and a bottom surface, a first end and a second end,

said top surface having a first section and a second section,

said first section of said top surface being lower in height than said second section,

at least one second ramp portion,

said at least one second ramp portion having a top surface and a bottom surface, and

Docket No. JHM1174

Page 3

wherein said method comprises:

positioning said first ramp portion adjacent tires of a vehicle,

moving said vehicle until said tires are on said second section of said top surface,

placing at least one second ramp portion on said first section of said first ramp portion,

moving said vehicle until said tires are resting on said at least one second ramp portion, and

wherein the method further comprises:

adding an additional second ramp portion by placing said additional second ramp portion on said second section of said top surface of said first ramp portion,

moving said vehicle until said tires are resting on said additional second ramp portion.